

--RELATED PATENT APPLICATIONS

A1
This is a divisional of patent application no. 09/223,519 filed December 30,
1998.--

In The Claims

Please Cancel Claims 1-10 and add the following new claims:

11. A data storage system wherein end-user data is transferred between a host computer and a bank of disk drives through an interface, such interface, comprising:

a memory;

a plurality of directors, at least one front-end one of the directors being in communication with the host computer and at least one rear-end one of the directors being in communication with the bank of disk drives, each one of the directors comprising:

a central processing unit;

an interface state data bus section, for carrying interface state data, such interface state data bus section being in communication with: both the at least one front-end one and the at least one rear-end one of the directors; and the memory;

a plurality of end-user data busses, for carrying end-user data, each one of the plurality of end-user data busses having a first end coupled to a corresponding one of the plurality of directors and a second end coupled to the memory; and

wherein the central processing units of such plurality of directors control the end-user data transfer between the host computer and the bank of disk drives through the memory via the end-user data busses in response to interface state data generated by the

C
A2
Pent

directors, such generated interface state data being transferred among the directors through the memory via the interface state data bus section.

2 12. The system recited in claim 11 wherein the end-users data busses are serial busses.

3 13. The system recited in claim 11 wherein the interface state data bus section includes parallel busses.

4 14. The system recited in claim 13 wherein the parallel busses are coupled to the directors in a multi-drop configuration.

5 15. The system recited in claim 13 wherein the end-user data busses are serial busses.

6 16. The system recited in claim 15 wherein the parallel busses are coupled to the directors in a multi-drop configuration.

7 17. The system recited in claim 11 including a coupling node and wherein each the memory has a plurality of regions and wherein the each one of the end-user data buses is coupled to the plurality of regions selectively through coupling node.

8 18. The system recited in claim 17 wherein the coupling node includes a cross-bar switch.

C
19. The system recited in claim ³13 wherein the interface state data bus section includes a plurality of parallel busses, each one thereof being coupled to a one of the plurality of directors and to the memory.

10 20. A method of operating a data storage system wherein end-user data is transferred between a host computer and a bank of disk drives through an interface, such method comprising:

providing a memory;

providing a plurality of directors, each one of the directors having a central processing unit, at least one front-end one of the directors being in communication with the host computer and at least one rear-end one of the directors being in communication with the bank of disk drives;

providing a plurality of interface state data busses for carrying interface state data, such interface state data busses being in communication with: both the at least one front-end one and the at least one rear-end one of the directors; and the memory;

providing a plurality of end-user data busses, for carrying end-user data, each one of the plurality of end-user data busses having a first end coupled to a corresponding one of the plurality of directors and a second end coupled to the memory; and

wherein the central processing units of such plurality of directors control the end-user data transfer between the host computer and the bank of disk drives through the memory via the end-user data busses in response to interface state data generated by the directors, such generated interface state data being transferred among the directors through the memory via the interface state data bus.

11 21. A data storage system wherein end-user data is transferred between a host computer and a bank of disk drives through an interface, such interface, comprising:

a memory;

a plurality of directors, each one having a central processing unit, at least one front-end one of the directors being in communication with the host computer and at least one rear-end one of the directors being in communication with the bank of disk drives;

an interface state data bus section, for carrying interface state data, such interface state data bus section being in communication with the at least one front-end one and the at least one rear-end one of the directors;

a plurality of end-user data busses, for carrying end-user data, each one of the plurality of end-user data busses having a first end coupled to a corresponding one of the plurality of directors and a second end coupled to the memory; and

wherein such central processing units of the plurality of directors control the end-user data transfer between the host computer and the bank of disk drives through the memory via the end-user data busses in response to interface state data generated by the directors, such generated interface state data being transferred among the directors via the interface state data bus section.

12 22. The system recited in claim 21 wherein the end-users data busses are serial busses.

13 23. The system recited in claim 21 wherein the interface state data bus section includes parallel busses.

- 14/24. The system recited in claim ¹³23 wherein the parallel busses are coupled to the directors in a multi-drop configuration.
- 15/25. The system recited in claim ¹³23 wherein the end-user data busses are serial busses.
- 16/26. The system recited in claim ¹⁵25 wherein the parallel busses are coupled to the directors in a multi-drop configuration.
- 17/27. The system recited in claim ¹¹21 including a coupling node and wherein each the memory has a plurality of regions and wherein the each one of the end-user data buses is coupled to the plurality of regions selectively through coupling node.
- 18/28. The system recited in claim ¹³23 wherein the interface state data bus section includes a plurality of parallel busses, each one thereof being coupled to a one of the plurality of directors and to the memory.
- 19/29. A method of operating a data storage system wherein end-user data is transferred between a host computer and a bank of disk drives through an interface, such method comprising:
- providing a memory;
 - providing a plurality of directors each one of the directors having a central processing unit, at least one front-end one of the directors being in communication with

the host computer and at least one rear-end one of the directors being in communication with the bank of disk drives;

providing an interface state data section for carrying interface state data, such interface state data section being in communication with the at least one front-end one and the at least one rear-end one of the directors;

providing a plurality of end-user data busses, for carrying end-user data, each one of the plurality of end-user data busses having a first end coupled to a corresponding one of the plurality of directors and a second end coupled to the memory; and

wherein such central processing units of the plurality of directors control the end-user data transfer between the host computer and the bank of disk drives and the memory via the end-user data busses in response to interface state data generated by the directors, such generated interface state data being transferred among the directors via the interface state data section.

²⁰ 30 A data storage system wherein end-user data is transferred between a host computer and a bank of disk drives through an interface, such interface, comprising:

a memory;

a plurality of directors, each one thereof having a central processing unit, a front-end portion of such plurality of directors being in communication with the host computer, and a rear end portion of such plurality of directors being in communication with the bank of disk drives;

1
an interface state data bus section, for carrying interface state data, such interface state data bus section being in communication with both the front-end portion of the plurality of directors and the rear end portion of the plurality of directors;

AD
Cord
a plurality of end-user data busses, for carrying end-user data, each one of the plurality of end-user data busses having a first end coupled to a corresponding one of the plurality of directors and a second end coupled to the memory; and

wherein the central processing units of such plurality of directors control the end-user data transfer between the host computer and the bank of disk drives through the memory via the end-user data busses in response to interface state data generated by the directors, such generated interface state data being transferred among the directors via the interface state data bus section.

205441-01300
202310-142500
21/31. The system recited in claim ²⁰30 wherein the end-users data busses are serial busses.

22/32. The system recited in claim ²⁰30 wherein the interface state data bus section includes parallel busses.

23/33. The system recited in claim ²²32 wherein the parallel busses are coupled to the directors in a multi-drop configuration.

24/34. The system recited in claim ²²32 wherein the end-user data busses are serial busses.

- 25/ 35. The system recited in claim 34²⁴ wherein the parallel busses are coupled to the directors in a multi-drop configuration.
- 26/ 36. The system recited in claim 30²⁰ including a coupling node and wherein each the memory has a plurality of regions and wherein the each one of the end-user data buses is coupled to the plurality of regions selectively through coupling node.
- 27/ 37. The system recited in claim 36²⁶ wherein the coupling node includes a cross-bar switch.
- 28/ 38. The system recited in claim 32²⁷ wherein the interface state data bus section includes a plurality of parallel busses, each one thereof being coupled to a one of the plurality of directors and to the memory.
- 29/ 39. A method of operating a data storage system wherein end-user data is transferred between a host computer and a bank of disk drives through an interface, such method comprising:
- providing a memory;
 - providing a plurality of directors, each one of the directors having a central processing unit, a front end portion of the directors being in communication with the host computer and a rear end portion of the directors being in communication with the bank of disk drives;

20021014245001

C1

R2
Card

providing an interface state data section for carrying interface state data, such interface state data section being in communication with the front end portion of the directors and the rear end portion of the directors;

providing a plurality of end-user data busses, for carrying end-user data, each one of the plurality of end-user data busses having a first end coupled to a corresponding one of the plurality of directors and a second end coupled to the memory; and

wherein the central processing units of such plurality of directors control the end-user data transfer between the host computer and the bank of disk drives and the memory via the end-user data busses in response to interface state data generated by the directors, such generated interface state data being transferred among the directors via the interface state data section.

30 40. A data storage system wherein end-user data is transferred between a host computer and a bank of disk drives through an interface, such interface, comprising:

a memory;

a plurality of directors, comprising:

a plurality of front-end directors, each one of such front-end directors having a central processing unit, such plurality of front end directors being in communication with the host computer, and

a plurality of rear end directors, each one of the rear-end directors having a central processing unit, such plurality of rear end directors being in communication with the bank of disk drives;

10054241-012202

AS
C1

an interface state data bus section, for carrying interface state data, such interface state data bus section being in communication with both the front-end portion of the plurality of directors and the rear end portion of the plurality of directors;

a plurality of end-user data busses, for carrying end-user data, each one of a first portion of the plurality of end-user data busses having a first end coupled to a corresponding one of the plurality of front end directors and a second end coupled to the memory and each one of a second portion of the plurality of end user data buses having a first end coupled to a corresponding one of the plurality of rear end directors and a second end coupled to the memory; and

wherein the central processing units of such plurality of directors control the end-user data transfer between the host computer and the bank of disk drives through the memory via the end-user data busses in response to interface state data generated by the directors, such generated interface state data being transferred among the directors via the interface state data bus section.

³¹ 41. The system recited in claim ³⁰ 40 wherein the first portion of the end-users data busses comprises a plurality of serial busses.

³² 42. The system recited in claim ³⁰ 40 wherein the second portion of the interface state data bus section comprises a plurality of serial busses.

³³ 43. The system recited in claim ³² 42 wherein the first portion of the end-users data busses comprises a plurality of serial busses.

34
44. A method of operating a data storage system wherein end-user data is transferred between a host computer and a bank of disk drives through an interface, such method comprising:

providing a memory;

providing a plurality of directors, such plurality of directors comprising:

a plurality of front end directors, each one thereof having a central processing unit, such plurality of front end directors being in communication with the host computer, and;

a plurality of rear end directors, each one thereof having a central processing unit, such plurality of rear end directors being in communication with the bank of disk drives;

providing an interface state data section for carrying interface state data, such interface state data section being in communication with the plurality of front end directors and the plurality of rear end directors;

providing a plurality of end-user data busses, for carrying end-user data, each one of a first portion of the plurality of end-user data busses having a first end coupled to a corresponding one of the plurality of front end directors and a second end coupled to the memory and each one of a second portion of the plurality of end user buses having a first end coupled to a corresponding one of the plurality of the rear end directors and a second end coupled to the memory;

wherein the central processing units of such plurality of directors control the end-user data transfer between the host computer and the bank of disk drives and the memory via the end-user data busses in response to interface state data generated by the

10054241.013202

C
P2
cont

Application No.

Filing Date:

Attorney Docket No.: EMC2-078AUS

directors, such generated interface state data being transferred among the directors via the interface state data section.

³⁵45. The method recited in claim ³⁴44 wherein the first portion of the end-users data busses is provided with a plurality of serial busses.

³⁶46. The method recited in claim ³⁴44 wherein the second portion of the interface state data bus section is provided with a plurality of serial busses.

³⁷47. The method recited in claim ³⁶46 wherein the first portion of the end-users data busses is provided with a plurality of serial busses.

The Assistant Commissioner is hereby authorized to charge payment of any additional fees associated with this communication or credit any overpayment to Deposit Account No. 50-0845.

Respectfully submitted,

Date

1/22/02

Richard M. Sharkansky
Attorney for Applicant(s)
Registration No. 25,800
Daly, Crowley & Mofford, LLP
275 Turnpike Street, Suite 101
Canton, MA 02021-2310
Telephone (781) 401-9988 x23
Facsimile (781) 401-9966

26

A